

---

**HEADCEL S2016**

---

Version 1.3

April 2019

***Modified Cellulose Ether for cement-based systems***

Headcel S2016 is developed for cement-based dry mortar products including advanced tile adhesive, cement plaster. It allows manufacturing tiles adhesives with exceptional slip resistance and open times. Due to its good anti-slip property it can be used in high end tile adhesive product.

It also imparts good workability and enhances water retention. It is compatible with all conventional mineral and organic binders.

- ✓ Good water retention
- ✓ Good workability
- ✓ Very good anti-slip
- ✓ Long open time

In drymix mortar system.

Typical addition level for ceramic tile adhesive : 0.2 – 0.5%

Chemical basis :	modified cellulose derivatives
Viscosity <sup>1)</sup> :	20,000-30,000 mPa·s
Form:	powder
Moisture content :	max. 7 %

<sup>1)</sup> 2 % solution; on dry basis; Brookfield RVT; 20 rpm, 20°C.

**Packing:**

25kg, paper-plastic composite bags or kraft paper valve bags . Other types of packages, such as big bags, can be supplied if required. 20'FCL:12 tons with pallets or 14 tons without pallets

Page 1 of 2

---

The products and related information provided by ShanDong Head Co.,Ltd are for **manufacturing use only**. ShanDong Head makes no express, implied, or other representation, warranty, or guarantee concerning (i) the handling, use, or application of such products, whether alone, in combination with other products, or otherwise, (ii) the completeness, definitiveness, or adequacy of such information for user's or other purposes, (iii) the quality of such products, except that such products are of Head's standard quality. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Read and understand the Material Safety Data Sheet (MSDS) before using this product.

Shandong Head does not recommend any use of its products that would violate any patent or other rights.