

Omya International AG P.O. Box CH-4665 Oftringen

+41 62 789 29 29 +41 62 789 20 77

www.omya.com

# Omyacarb® 60 - GZ

PRODUCTION SITE: GEBZE, Turkey

(certified ISO 9001, ISO 14001 and OHSAS 18001)

SHORT DESCRIPTION OF

THE PRODUCT:

Natural, high purity, easy to disperse calcium carbonate powder with good resistance to weather and ageing. Low oil absorption.

CHEMICAL ANALYSIS:	CaCO₃	98.5	%
	MgCO₃	1.5	%
	$Fe_2O_3$	0.05	%
	HCI insoluble content	0.5	%

SPECIFIC PRODUCT DATA: Fineness:

ilieliess.		
Residue on a 200 µm sieve (ISO 787-7)	0.5	%
Top cut (d98%)	168	μm
Median particle size (d50%)	24	μm
Particles < 2 µm	11	%
Optical properties:		
Brightness Ry (C/2°, DIN 53163)	93	%
CIE L*, a*, b* (ISO 11664-4)	97.5/0.08/1.2	
Yellowness index (DIN 6167)	2.5	
Moisture ex works (ISO 787-2)	0.5	%

GENERAL PRODUCT DATA: Apparent density, tamped (ISO 787-11) 1.35 g/ml pH value (ISO 787-9) 9.5

 Oil absorption (ISO 787-5)
 8 g/100g

 VO absorption (ISO 787-5)
 17 g/100g

# MAIN APPLICATIONS:

# **Paints**


- Interior and exterior emulsion paints

- Oil and synthetic resin systems

#### Building chemicals

- Adhesives
- Sealants
- Putties
- Special mortars and fillers
- Plasters and exterior coatings

# PARTICLE SIZE DISTRIBUTION (Malvern Mastersizer 2000):



The information contained in this Technical Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Omya believes to be reliable, however Omya makes no representation or warranty as to the completeness or accuracy thereof and Omya assumes no liability resulting from its use or for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgement as to the appropriateness of its use, and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.

edition: 27.07.2017
Product Information:
S08.03.01\_EN\_CORP\TRGZ
I81260\_00\_E
version: 9